

What makes Gizmow Different ...

New Gizmow steering wheel

Uses a steering wheel and so it is easy to use and familiar to drive

Gives full zero turn mowing capability keeping you mowing longer

The rear wheels are always driven

The machine can be turned at full speed

Better control on banks & hillsides because we steer the front wheels

Safer on the road and on trailers

Other Mowers

Stick steer ZTR's takes time to train operators and learn a new way of driving

Conventional mowers require 3 point turns slowing operation

Conventional mowers have differentials that transfer drive to the outer wheel reducing traction

Stick steer ZTR's can tear turf at full speed

Castor front wheels on stick steer ZTR's steer the machine downwards on slopes

ZTR's awkward to control and drive up ramps.

SPECIFICATION Model F6127DI-EU

ENGINE

Model	Vanguard DM950D
No of Cylinders	3
Cubic capacity	20KW (27HP)
Fuel tank capacity	37litres

DIMENSIONS

Overall length	2300 mm
Overall width	1600 mm
Overall height (Ex ROPS)	1900mm (1200 mm)
Turning radius	Zero turning radius (ZTR)
Weight	800 kg (780kg)
Wheel base	1296 mm
Tyre size - front	13 x 5.00 - 6
Tyre size - rear	24 x 12.00 - 12

TRANSMISSION

Transmission system	Hydrostatic
Speed control	Forward / reverse foot pedals
Forward speed range	0 - 16 Km/h
Reverse Speed range	0 - 8 Km/h
Pump & wheel motors	Hydrogear
Brake type	External expanding shoe
PTO clutch	Borg Warner Mag 270Nm 28.5mm bore CCW

*The company reserves the right to change the above specification without notice
This brochure is for descriptive purposes only.

OTHER STANDARD FEATURES

Adjustable suspension seat	Standard
Kevlar belts	Standard
Horn	Standard
Hour Meter / Tachometer	Standard
Fuel tank guards	Standard
Cup Holder	Standard
Front fender & lashing points	Standard
Tool Box	Standard

OPTIONAL EQUIPMENT

ROPS (Folding)	Optional
Road lighting kit	Optional
Amber beacon and mount	Optional
Mulch Kit	Optional

MOWER SPECIFICATION

Construction	4.5 mm (7 Gauge) Steel
Mounting system of mower	Parallel linkage
Blade Drive method	Hexagonal Kevlar Belt
Belt tensioning	Automatic
Cutting width	1550 mm
Cutting height	25 mm - 145 mm
No of blades	3 Marbain steel (1 Contra-rotating)
Discharge	Rear
Castoring anti-scalp rollers	Standard



on banks the road verges around obstacles

GIZMOW

Regent House, Whitewalls Ind. Estate, Colne. BB8 8LJ UK

Tel +44 (0) 1282 856828 Fax +44 (0) 1282 860555
Email sales@gizmow-europe.com Website www.gizmow.com

GIZMOW

FORMULA

the zero-turn with a **steering wheel**



Easy to use
Increased productivity of ZTR
Turns at full speed
Reduces turf damage
Better traction on banks
Safer on roads



Powered by
VANGUARD
COMMERCIAL POWER
DIESEL

